Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCALEOVIEW T15-1
15’’ LCD TFT Display

Issue September 2004

Pages 2

Value display that does not compromise on quality features or style.
Featuring a space saving design that is perfect for home and office, it offers high contrast, good brightness and plug and play technology.

Reliability

- Guaranteed quality and stability
- Reliability of delivery
- Low power consumption
- Multi-level power management
- Experience service partners

- Usability
- Administrator is able to read inventory data
- Auto-adjust
- Integrated power supply
- Easy-to-use menu
- Plug & Play
- Analogue interface
- Standardised mounting interface
- Integrated audio
- Fast response time

- Ergonomics
- Optimum flicker-free and distortion-free ergonomics
- Excellent colour purity
- Outstanding brightness uniformity
- Extremely wide viewing angle
- Integrated speakers

- High contrast and excellent focus
- Environmental friendly with low-radiation
- Immunity to external electromagnetic fields

- Diversity
- Displays for differentiated demands
- Meets highest demands in terms of ergonomics, usability and resolution
- Comparable with 17-inch CRT display

- Valuable and accepted Brand
- Profiting from the experience as leading European consumer brand
- Strong cooperation with leading edge technology suppliers for latest technologies
- Strong relationship with internationally acting retail partners for fast delivery and best support

- Market innovator
- Leading edge technology
- High quality and stylish design
- Latest technologies
- Continuity in product availability

Visible screen diagonal	**15 inch** (38 cm)
Graphics display (dependent on graphics processor)	
Pixels	1024 x 768
Pixels *)	800 x 600
Pixels *)	640 x 480
*) expanded	
Text display (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
Picture size	304 x 228 mm
Frequencies	
Horizontal	28 - 63 kHz
Vertical	55 - 78 Hz
Brightness typical	350 cd/m^2
Contrast typical	450:1
Viewing angle typical	
Horizontal	120°
Vertical	110°
Response time typical	23 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Auto balance	
Activate factory settings	
Menu language	
Base	
Tilt angle	+20 ° (back)
Audio characteristics	
volume control	digital
Audio signal input (from PC)	3.5 mm stereo phone jack
Sound output	1.5 W (L) + 1.5 W (R)

Electrical values	
Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Max.	33 W
Stand by	3 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Working	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D)	348 x 374 x 189 mm
Weight (Monitor only)	2.6 kg
Reliability	
MTBF (demonstrated)	50,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	40,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
Data cable (1.8 m) detachable on display	D-SUB (15-pin) audio cable (1.8 m)
Power cable (1.8 m)	For wall socket Euro-Schuko-Type CEE7
External power adapter	
Plug type on power adapter	IEC-320-C13
Special features	Standardized mounting interface according VESA FPMPMI (75 mm)
Order code	S26361-K973-V170

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers,09/2004

Published by

Fujitsu Siemens Computers
Hhttp://www.fujitsu-siemens.com/H

Company stamp